



ANSI 300LBS RF BLIND

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	i	T	K	d4	f	Bolt no.	d2	Kg / Pc
DN 15	½"	95	12.3	14.3	66.7	35	2	4	15	0.63
DN 20	¾"	117	13.1	15.1	82.5	43	2	4	19	1.02
DN 25	1"	124	15.5	17.5	88.9	51	2	4	19	1.37
DN 32	1¼"	133	17.1	19.1	98.4	64	2	4	19	1.77
DN 40	1½"	156	17.7	20.7	114.3	73	3	4	22	2.56
DN 50	2"	165	19.3	22.3	127	92	3	8	19	3.07
DN 65	2½"	190	22.4	25.4	149.2	105	3	8	22	4.68
DN 80	3"	210	25.6	28.6	168.3	127	3	8	22	6.68
DN 90	3½"	229	27.2	30.2	184	140	3	8	22	8.56
DN 100	4"	254	28.8	31.8	200	157	3	8	22	11.29
DN 125	5"	279	32	35	234.9	186	3	8	22	15.32
DN 150	6"	318	33.6	36.6	269.9	216	3	12	22	20.72
DN 200	8"	381	38.3	41.3	330.2	270	3	12	25	34.04
DN 250	10"	444	44.7	47.7	387.3	324	3	16	29	52.86
DN 300	12"	521	46.8	50.8	450.8	381	4	16	32	77.61
DN 350	14"	584	50	54	514.3	413	4	20	32	103.61
DN 400	16"	648	53.2	57.2	571.5	470	4	20	35	135.90
DN 450	18"	711	56.4	60.4	628.6	533	4	24	35	173.54
DN 500	20"	775	59.5	63.5	685.8	584	4	24	35	219.18
DN 600	24"	914	64.9	69.9	812.8	692	5	24	41	334.76