



PN 40 RF BLIND

| Size | | Flange | | | Raised Face | | Drilling | | Weight |
|--------|------|--------|------|-----|-------------|---|----------|----|---------|
| mm | inch | D | b | K | d4 | f | Bolt no. | d2 | Kg / Pc |
| DN 15 | ½" | 95.0 | 12.0 | 65 | 45 | 2 | 4 | 14 | 0.64 |
| DN 20 | ¾" | 105.0 | 14.0 | 75 | 58 | 2 | 4 | 14 | 0.93 |
| DN 25 | 1" | 115.0 | 14.0 | 85 | 68 | 2 | 4 | 14 | 1.14 |
| DN 32 | 1¼" | 140.0 | 16.0 | 100 | 78 | 2 | 4 | 18 | 1.89 |
| DN 40 | 1½" | 150.0 | 15.0 | 110 | 88 | 3 | 4 | 18 | 2.12 |
| DN 50 | 2" | 165.0 | 17.0 | 125 | 102 | 3 | 4 | 18 | 2.93 |
| DN 65 | 2½" | 185.0 | 19.0 | 145 | 122 | 3 | 8 | 18 | 4.00 |
| DN 80 | 3" | 200.0 | 21.0 | 160 | 138 | 3 | 8 | 18 | 5.22 |
| DN 100 | 4" | 235.0 | 23.0 | 190 | 162 | 3 | 8 | 22 | 7.81 |
| DN 125 | 5" | 270.0 | 25.0 | 220 | 188 | 3 | 8 | 26 | 11.12 |
| DN 150 | 6" | 300.0 | 27.0 | 250 | 218 | 3 | 8 | 26 | 15.04 |
| DN 200 | 8" | 375.0 | 33.0 | 320 | 285 | 3 | 12 | 30 | 28.07 |
| DN 250 | 10" | 450.0 | 39.0 | 385 | 345 | 3 | 12 | 33 | 48.02 |
| DN 300 | 12" | 515.0 | 48.0 | 450 | 410 | 4 | 16 | 33 | 77.91 |
| DN 350 | 14" | 580.0 | 50.0 | 510 | 465 | 4 | 16 | 36 | 103.22 |
| DN 400 | 16" | 660.0 | 56.0 | 585 | 535 | 4 | 16 | 39 | 149.89 |
| DN 450 | 18" | 685.0 | 62.0 | 610 | 560 | 4 | 20 | 39 | 176.45 |
| DN 500 | 20" | 755.0 | 68.0 | 670 | 615 | 4 | 20 | 42 | 234.83 |
| DN 600 | 24" | 890.0 | 80.0 | 795 | 735 | 4 | 20 | 48 | 383.42 |