



PN 16 RF BLIND

Size		Flange			Raised Face		Drilling		Weight
mm	inch	D	b	K	d4	f	Bolt no.	d2	Kg / Pc
DN 10	3/8"	90	12	60	40	2	4	14	0.56
DN 15	1/2"	95	12	65	45	2	4	14	0.64
DN 20	3/4"	105	14	75	58	2	4	14	0.93
DN 25	1"	115	14	85	68	2	4	14	1.14
DN 32	1 1/4"	140	14	100	78	2	4	18	1.66
DN 40	1 1/2"	150	14	110	88	2	4	18	1.94
DN 50	2"	165	15	125	102	3	4	18	2.60
DN 65	2 1/2"	185	15	145	122	3	4	18	3.34
DN 80	3"	200	17	160	138	3	8	18	4.30
DN 100	4"	220	17	180	158	3	8	18	5.29
DN 125	5"	250	19	210	188	3	8	18	7.71
DN 150	6"	285	19	240	212	3	8	23	9.91
DN 200	8"	340	21	295	260	3	12	23	15.48
DN 250	10"	405	23	355	320	3	12	27	24.05
DN 300	12"	460	25	410	380	3	12	27	34.13
DN 350	14"	520	26	470	438	4	16	27	46.47
DN 400	16"	580	28	525	490	4	16	30	61.85
DN 450	18"	640	30	585	548	4	20	30	80.29
DN 500	20"	715	32	650	610	4	20	33	106.33
DN 600	24"	840	36	770	690	4	20	36	163.51