



## PN 16 FF

Size		Flange				Drilling		Weight
mm	inch	D	A	b	K	Bolt no.	d2	Kg / Pc
DN 10	3/8"	90	18	14	60	4	14	0.61
DN 15	1/2"	95	22	14	65	4	14	0.67
DN 20	3/4"	105	27.5	16	75	4	14	0.94
DN 25	1"	115	34.5	16	85	4	14	1.12
DN 32	1 1/4"	140	43.5	18	100	4	18	1.83
DN 40	1 1/2"	150	49.5	18	110	4	18	2.09
DN 50	2"	165	61.5	20	125	4	18	2.75
DN 65	2 1/2"	185	77.5	20	145	4	18	3.34
DN 80	3"	200	90.5	20	160	8	18	3.62
DN 100	4"	220	116	22	180	8	18	4.41
DN 125	5"	250	141.5	22	210	8	18	5.44
DN 150	6"	285	170.5	24	240	8	22	7.18
DN 200	8"	340	221.5	26	295	12	22	9.79
DN 250	10"	405	276.5	29	355	12	26	14.29
DN 300	12"	460	327.5	32	410	12	26	19.09
DN 350	14"	520	359	35	470	16	26	28.36
DN 400	16"	580	411	38	525	16	30	36.07
DN 450	18"	640	462	42	585	20	30	46.39
DN 500	20"	715	513.5	46	650	20	33	64.39
DN 600	24"	840	616.5	52	770	20	36	96.59