



## DIN 2501 PN 16 RF

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	22.0	14	65	45	2	4	14	0.60
DN 20	¾"	105	27.6	16	75	58	2	4	14	0.86
DN 25	1"	115	34.4	16	85	68	2	4	14	1.02
DN 32	1¼"	140	43.1	16	100	78	2	4	18	1.48
DN 40	1½"	150	49.0	16	110	88	3	4	18	1.61
DN 50	2"	165	61.1	18	125	102	3	4	18	2.19
DN 65	2½"	185	77.1	18	145	122	3	4	18	2.68
DN 80	3"	200	90.3	20	160	138	3	8	18	3.29
DN 100	4"	220	115.9	20	180	158	3	8	18	3.63
DN 125	5"	250	141.6	22	210	188	3	8	18	4.98
DN 150	6"	285	170.5	22	240	212	3	8	23	5.94
DN 200	8"	340	221.8	24	295	268	3	12	23	8.24
DN 250	10"	405	276.2	26	355	320	3	12	27	11.75
DN 300	12"	460	327.6	28	410	378	4	12	27	15.10
DN 350	14"	520	359.7	30	470	438	4	16	27	22.40
DN 400	16"	580	411.0	32	525	490	4	16	30	28.34
DN 450	18"	640	462.3	32	585	548	4	20	30	33.03
DN 500	20"	715	513.6	34	650	610	4	20	33	44.66
DN 600	24"	840	615.0	36	770	725	5	20	36	62.51