



JIS 20K RF

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	95	22.2	14	70	52	1	4	15	0.63
DN 20	¾"	100	27.7	16	75	58	1	4	15	0.79
DN 25	1"	125	34.5	16	90	70	1	4	19	1.23
DN 32	1¼"	135	43.2	18	100	80	2	4	19	1.54
DN 40	1½"	140	49.1	18	105	85	2	4	19	1.62
DN 50	2"	155	61.1	18	120	100	2	8	19	1.80
DN 65	2½"	175	77.1	20	140	120	2	8	19	2.54
DN 80	3"	200	90	22	160	135	2	8	23	3.56
DN 100	4"	225	115.4	24	185	160	2	8	23	4.66
DN 125	5"	270	141.2	26	225	195	2	8	25	7.36
DN 150	6"	305	166.6	28	260	230	2	12	25	9.62
DN 200	8"	350	218	30	305	275	2	12	25	12.06
DN 250	10"	430	269.5	34	380	345	2	12	27	21.11
DN 300	12"	480	321	36	430	395	3	16	27	24.66
DN 350	14"	540	358.1	40	480	440	3	16	33	34.69
DN 400	16"	605	409	46	540	495	3	16	33	49.79
DN 450	18"	675	460	48	605	560	3	20	33	63.90
DN 500	20"	730	511	50	660	615	3	20	33	75.03
DN 550	22"	795	562	52	720	670	3	20	39	89.29
DN 600	24"	845	613	54	770	720	3	24	39	98.07