



Section "A - A"



### PN40 RF

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	b	K	d4	f	Bolt no.	d2	Kg / Pc
DN 15	½"	95.0	22.0	12.0	65	45	2	4	14	0.60
DN 20	¾"	105.0	27.5	14.0	75	58	2	4	14	0.86
DN 25	1"	115.0	34.5	14.0	85	68	2	4	14	1.02
DN 32	1¼"	140.0	43.5	16.0	100	78	2	4	18	1.68
DN 40	1½"	150.0	49.5	15.0	110	88	3	4	18	1.84
DN 50	2"	165.0	61.5	17.0	125	102	3	4	18	2.46
DN 65	2½"	185.0	77.5	19.0	145	122	3	8	18	3.18
DN 80	3"	200.0	90.5	21.0	160	138	3	8	18	4.01
DN 100	4"	235.0	116.0	23.0	190	162	3	8	22	5.64
DN 125	5"	270.0	141.5	25.0	220	188	3	8	26	7.64
DN 150	6"	300.0	170.5	27.0	250	218	3	8	26	9.64
DN 200	8"	375.0	221.5	33.0	320	285	3	12	30	17.12
DN 250	10"	450.0	276.5	39.0	385	345	3	12	33	28.11
DN 300	12"	515.0	327.5	48.0	450	410	4	16	33	43.34
DN 350	14"	580.0	359.0	50.0	510	465	4	16	36	60.07
DN 400	16"	660.0	411.0	56.0	585	535	4	16	39	87.05
DN 450	18"	685.0	462.0	62.0	610	560	4	20	39	89.11
DN 500	20"	755.0	513.5	68.0	670	615	4	20	42	117.12
DN 600	24"	890.0	616.5	80.0	795	735	4	20	48	185.48