



DIN 2635 PN 40 WNRF

Size		Pipe	Flange						Neck				Raised Face		Drilling		Weight
mm	inch	d1	D	A	T	T-F	K	h1	h2	d3	s	r	F	G	Bolt No.	H	Kg / Pc
DN 15	½"	21.3	95	17.3	16	14	65	38	6	32	2.0	4	2	45	4	14	0.76
DN 20	¾"	26.9	105	22.3	18	16	75	40	6	40	2.3	4	2	58	4	14	1.08
DN 25	1"	33.7	115	28.5	18	16	85	40	6	45	2.6	4	2	68	4	14	1.29
DN 32	1¼"	42.4	140	37.2	18	16	100	42	6	56	2.6	6	2	78	4	18	1.88
DN 40	1½"	48.3	150	43.1	18	15	110	45	7	64	2.6	6	3	88	4	18	2.10
DN 50	2"	60.3	165	54.5	20	17	125	48	8	75	2.9	6	3	102	4	18	2.80
DN 65	2½"	76.1	185	70.3	22	19	145	52	10	90	2.9	6	3	122	8	18	3.64
DN 80	3"	88.9	200	82.5	24	21	160	58	12	105	3.2	8	3	138	8	18	4.67
DN 100	4"	114.3	235	107.1	24	21	190	65	12	134	3.6	8	3	162	8	22	6.33
DN 125	5"	139.7	270	131.7	26	23	220	68	12	162	4.0	8	3	188	8	26	8.70
DN 150	6"	168.3	300	159.3	28	25	250	75	12	192	4.5	10	3	218	8	26	11.40
DN 200	8"	219.1	375	206.5	34	31	320	88	16	244	6.3	10	3	285	12	30	20.68
DN 250	10"	273.0	450	258.8	38	35	385	105	18	306	7.1	12	3	345	12	33	33.65
DN 300	12"	323.9	515	307.9	42	38	450	115	18	362	8.0	12	4	410	16	33	46.99
DN 350	14"	355.6	580	338.0	46	42	510	125	20	408	8.8	12	4	465	16	36	68.37
DN 400	16"	406.4	660	384.4	50	46	585	135	20	462	11.0	12	4	535	16	39	97.65
DN 450	18"	457.0	685	432.0	50	46	610	135	20	500	12.5	12	4	560	20	39	95.31
DN 500	20"	508.0	755	479.6	52	48	670	140	20	562	14.2	12	4	615	20	42	122.10
DN 600	24"	610.0	890	578.0	72	67	795	150	20	666	16.0	12	5	735	20	48	209.32