



## JIS 5K FF BLIND

| Size   |      | Flange |    |     | Drilling |    | Weight  |
|--------|------|--------|----|-----|----------|----|---------|
| mm     | inch | D      | T  | K   | Bolt no. | H  | Kg / Pc |
| DN 15  | ½"   | 80     | 9  | 60  | 4        | 12 | 0.32    |
| DN 20  | ¾"   | 85     | 10 | 65  | 4        | 12 | 0.41    |
| DN 25  | 1"   | 95     | 10 | 75  | 4        | 12 | 0.52    |
| DN 32  | 1¼"  | 115    | 12 | 90  | 4        | 15 | 0.92    |
| DN 40  | 1½"  | 120    | 12 | 95  | 4        | 15 | 1.00    |
| DN 50  | 2"   | 130    | 14 | 105 | 4        | 15 | 1.39    |
| DN 65  | 2½"  | 155    | 14 | 130 | 4        | 15 | 2.01    |
| DN 80  | 3"   | 180    | 14 | 145 | 4        | 19 | 2.69    |
| DN 100 | 4"   | 200    | 16 | 165 | 8        | 19 | 3.68    |
| DN 125 | 5"   | 235    | 16 | 200 | 8        | 19 | 5.19    |
| DN 150 | 6"   | 265    | 18 | 230 | 8        | 19 | 7.51    |
| DN 200 | 8"   | 320    | 20 | 280 | 8        | 23 | 12.17   |
| DN 250 | 10"  | 385    | 22 | 345 | 12       | 23 | 19.35   |
| DN 300 | 12"  | 430    | 22 | 390 | 12       | 23 | 24.35   |
| DN 350 | 14"  | 480    | 24 | 435 | 12       | 25 | 33.17   |
| DN 400 | 16"  | 540    | 24 | 495 | 16       | 25 | 41.90   |
| DN 450 | 18"  | 605    | 24 | 555 | 16       | 25 | 52.98   |
| DN 500 | 20"  | 655    | 24 | 605 | 20       | 25 | 61.98   |
| DN 550 | 22"  | 720    | 26 | 665 | 20       | 27 | 81.22   |
| DN 600 | 24"  | 770    | 26 | 715 | 20       | 27 | 93.23   |