



JIS 5K RF

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	T	K	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	80	22.2	9	60	48	1	4	12	0.28
DN 20	¾"	85	27.7	10	65	52	1	4	12	0.34
DN 25	1"	95	34.5	10	75	62	1	4	12	0.42
DN 32	1¼"	115	43.2	12	90	72	2	4	15	0.69
DN 40	1½"	120	49.1	12	95	78	2	4	15	0.73
DN 50	2"	130	61.1	14	105	88	2	4	15	0.96
DN 65	2½"	155	77.1	14	130	112	2	4	15	1.36
DN 80	3"	180	90	14	145	125	2	4	19	1.79
DN 100	4"	200	115.4	16	165	145	2	8	19	2.16
DN 125	5"	235	141.2	16	200	180	2	8	19	2.97
DN 150	6"	265	166.6	18	230	210	2	8	19	4.13
DN 200	8"	320	218	20	280	255	2	8	23	5.87
DN 250	10"	385	269.5	22	345	320	2	12	23	8.96
DN 300	12"	430	321	22	390	365	3	12	23	9.46
DN 350	14"	480	358.1	24	435	405	3	12	25	12.99
DN 400	16"	540	409	24	495	465	3	16	25	15.79
DN 450	18"	605	460	24	555	525	3	16	25	20.00
DN 500	20"	655	511	24	605	575	3	20	25	21.53
DN 550	22"	720	562	26	665	635	3	20	27	28.43
DN 600	24"	770	613	26	715	685	3	20	27	30.62