



PN10 RF

Size		Flange				Raised Face		Drilling		Weight
mm	inch	D	A	b	K	d4	f	Bolt no.	d2	Kg / Pc
DN 10	3/8"	90	18	12	60	40	2	4	14	0.54
DN 15	1/2"	95	22	12	65	45	2	4	14	0.60
DN 20	3/4"	105	27.5	14	75	58	2	4	14	0.86
DN 25	1"	115	34.5	14	85	68	2	4	14	1.02
DN 32	1 1/4"	140	43.5	16	100	78	2	4	18	1.68
DN 40	1 1/2"	150	49.5	15	110	88	3	4	18	1.84
DN 50	2"	165	61.5	17	125	102	3	4	18	2.46
DN 65	2 1/2"	185	77.5	17	145	122	3	4	18	3.00
DN 80	3"	200	90.5	17	160	138	3	8	18	3.28
DN 100	4"	220	116	19	180	162	3	8	18	4.05
DN 125	5"	250	141.5	19	210	188	3	8	18	4.98
DN 150	6"	285	170.5	21	240	212	3	8	22	6.58
DN 200	8"	340	221.5	21	295	268	3	8	22	8.58
DN 250	10"	395	276.5	23	350	320	3	12	22	11.00
DN 300	12"	445	327.5	22	400	370	4	12	22	12.32
DN 350	14"	505	359	24	460	430	4	16	22	19.01
DN 400	16"	565	411	28	515	482	4	16	28	25.49
DN 450	18"	615	462	32	565	532	4	20	28	31.31
DN 500	20"	670	513.5	34	620	585	4	20	28	37.69
DN 600	24"	780	616.5	37	725	685	5	20	31	50.73