



ANSI 150LBS SORF

Size		Flange					Slip On		Raised Face		Drilling		Weight
mm	inch	D	A	I	T	K	L	M	G	F	Bolt no.	H	Kg / Pc
DN 15	½"	89.0	22.3	15.9	9.5	60.3	4.8	30.2	34.9	1.6	4	15.9	0.40
DN 20	¾"	98.4	27.7	15.9	11.1	69.8	3.2	38.1	42.9	1.6	4	15.9	0.57
DN 25	1"	108.0	34.5	17.5	12.7	79.4	3.2	49.2	50.8	1.6	4	15.9	0.78
DN 32	1¼"	118.0	43.2	20.6	14.3	88.9	4.7	58.7	63.5	1.6	4	15.9	1.05
DN 40	1½"	127.0	49.5	22.2	15.9	98.4	4.7	65.1	73.0	1.6	4	15.9	1.33
DN 50	2"	152.0	62.0	25.4	17.4	120.6	6.4	77.8	92.1	1.6	4	19.0	2.06
DN 65	2½"	178.0	74.7	28.6	20.6	139.7	6.4	90.5	104.8	1.6	4	19.0	3.31
DN 80	3"	191.0	90.7	30.2	22.2	152.4	6.4	107.9	127.0	1.6	4	19.0	3.90
DN 100	4"	229.0	116.1	33.3	22.2	190.5	9.5	134.9	157.2	1.6	8	19.0	5.35
DN 125	5"	254.0	143.8	36.5	22.2	215.9	12.7	163.5	185.7	1.6	8	22.2	6.10
DN 150	6"	279.4	170.7	39.7	23.8	241.3	14.3	192.1	215.9	1.6	8	22.2	7.50
DN 200	8"	342.9	221.5	44.4	27.0	298.4	15.8	246.1	269.9	1.6	8	22.2	12.17
DN 250	10"	406.4	276.3	49.2	28.6	361.9	19.0	304.8	323.8	1.6	12	25.4	16.61
DN 300	12"	482.6	327.1	55.6	30.1	431.8	23.9	365.1	381.0	1.6	12	25.4	26.33
DN 350	14"	533.4	359.1	57.1	33.3	476.2	22.2	400.0	412.9	1.6	12	28.6	34.78
DN 400	16"	596.9	410.5	63.5	34.9	539.7	27.0	457.2	469.9	1.6	16	28.6	45.10
DN 450	18"	635.0	461.8	68.3	38.1	577.8	28.6	504.8	533.4	1.6	16	31.7	49.15
DN 500	20"	698.5	513.1	73.0	41.3	635.0	30.1	558.8	584.2	1.6	20	31.7	62.29
DN 600	24"	812.8	615.9	82.5	46.0	749.3	34.9	663.6	692.1	1.6	20	34.9	87.48