



### ANSI 300LBS SORF

Size		Flange					Slip On		Raised Face		Drilling		Weight
mm	inch	D	A	H	b	K	L	m	g	f	Bolt no.	d2	Kg / Pc
DN 15	½"	95.2	22.3	22.2	12.7	66.7	7.9	38.1	34.9	1.6	4	15.9	0.90
DN 20	¾"	117.5	27.7	25.4	14.3	82.5	9.5	47.6	42.9	1.6	4	19	1.40
DN 25	1"	123.8	34.5	27.0	15.9	88.9	9.5	54.0	50.8	1.6	4	19	1.40
DN 32	1¼"	133.3	43.2	27.0	17.4	98.4	8.0	63.5	63.5	1.6	4	19	1.80
DN 40	1½"	155.6	49.5	30.2	19.0	114.3	9.6	69.8	73.0	1.6	4	22.2	2.70
DN 50	2"	165.1	62.0	33.3	20.6	127	11.1	84.1	92.1	1.6	8	19	3.20
DN 65	2½"	190.5	74.7	38.1	23.8	149.2	12.7	100.0	104.8	1.6	8	22.2	4.50
DN 80	3"	209.5	90.7	42.9	27.0	168.3	14.3	117.5	127.0	1.6	8	22.2	5.90
DN 90	3½"	228.6	103.4	44.4	28.6	184.1	14.2	133.3	139.7	1.6	8	22.2	7.70
DN 100	4"	254.0	116.1	47.6	30.1	200	15.9	146.0	157.2	1.6	8	22.2	10.00
DN 125	5"	279.4	143.8	50.8	33.3	234.9	15.9	177.8	185.7	1.6	8	22.2	12.70
DN 150	6"	317.5	170.7	52.4	34.9	269.9	15.9	206.4	215.9	1.6	12	22.2	17.70
DN 200	8"	381.0	221.5	61.9	39.7	330.2	20.6	260.3	269.9	1.6	12	25.4	26.30
DN 250	10"	444.5	276.3	66.7	46.0	387.3	19.1	320.7	323.8	1.6	16	28.6	36.70
DN 300	12"	520.7	327.1	73.0	49.2	450.8	22.2	374.6	381.0	1.6	16	31.7	52.20
DN 350	14"	584.2	359.1	76.2	52.4	514.3	22.2	425.4	412.7	1.6	20	31.7	74.80
DN 400	16"	647.7	410.5	82.5	55.5	571.5	25.4	482.6	469.9	1.6	20	34.9	86.20
DN 450	18"	711.2	461.8	88.9	58.7	628.6	28.6	533.4	533.4	1.6	24	34.9	113.00
DN 500	20"	774.7	513.1	95.2	61.9	685.8	31.7	587.4	584.2	1.6	24	34.9	143.00
DN 600	24"	914.4	615.9	106.4	68.2	812.8	36.6	701.7	692.1	1.6	24	41.3	215.00