



ANSI 150LBS WNRF

Size		Pipe	Flange					Neck				Raised Face		Drilling	Weight		
mm	inch	d1	D	A	b	b - f	k	h1	h2	d3	s	r	f	d4	nr	d2	Kg / Pc
DN 15	½"	21.3	88.9	15.8	11.1	9.50	60.3	47.6	6.0	30.2	2.8	4	1.6	34.9	4	15.9	0.49
DN 20	¾"	26.7	98.4	20.9	12.7	11.10	69.8	52.4	6.0	38.1	2.9	4	1.6	42.9	4	15.9	0.72
DN 25	1"	33.5	107.9	26.7	14.3	12.70	79.4	55.6	6.0	49.2	3.4	4	1.6	50.8	4	15.9	1.04
DN 32	1¼"	42.2	117.5	35.1	15.9	14.30	88.9	57.1	6.0	58.7	3.6	6	1.6	63.5	4	15.9	1.37
DN 40	1½"	48.3	127.0	40.9	17.5	15.90	98.4	61.9	7.0	65.1	3.7	6	1.6	73.0	4	15.9	1.76
DN 50	2"	60.4	152.4	52.6	19.0	17.40	120.6	63.5	8.0	77.8	3.9	6	1.6	92.1	4	19.0	2.62
DN 65	2½"	73.1	177.8	62.7	22.2	20.60	139.7	69.8	10.0	90.5	5.2	6	1.6	104.8	4	19.0	4.17
DN 80	3"	88.9	190.5	78.0	23.8	22.20	152.4	69.8	10.0	107.9	5.5	8	1.6	127.0	4	19.0	5.00
DN 100	4"	114.3	228.6	102.4	23.8	22.20	190.5	76.2	12.0	134.9	6.0	8	1.6	157.2	8	19.0	6.98
DN 125	5"	141.2	254.0	128.3	23.8	22.20	215.9	88.9	12.0	163.5	6.5	8	1.6	185.7	8	22.2	8.78
DN 150	6"	168.4	279.4	154.2	25.4	23.80	241.3	88.9	12.0	192.1	7.1	10	1.6	215.9	8	22.2	10.84
DN 200	8"	219.2	342.9	202.7	28.6	27.00	298.4	101.6	16.0	246.1	8.3	10	1.6	269.9	8	22.2	17.85
DN 250	10"	273.0	406.4	254.5	30.2	28.60	361.9	101.6	16.0	304.8	9.3	12	1.6	323.8	12	25.4	24.34
DN 300	12"	323.8	482.6	304.8	31.7	30.10	431.8	114.3	16.0	365.1	9.5	12	1.6	381.0	12	25.4	37.22
DN 350	14"	355.6	533.4	336.6	34.9	33.30	476.2	127.0	16.0	400.0	9.5	12	1.6	412.9	12	28.6	49.35
DN 400	16"	406.4	596.9	387.4	36.5	34.90	539.7	127.0	16.0	457.2	9.5	12	1.6	469.9	16	28.6	61.12
DN 450	18"	457.2	635.0	438.2	39.7	38.10	577.8	139.7	16.0	504.8	9.5	12	1.6	533.4	16	31.7	69.55
DN 500	20"	508.0	698.5	489.0	42.9	41.30	635.0	144.5	16.0	558.8	9.5	12	1.6	584.2	20	31.7	85.98
DN 600	24"	609.6	812.8	590.6	47.6	46.00	749.3	152.4	18.0	663.6	9.5	12	1.6	692.1	20	34.9	116.76